






P20CS



P32CS



P20CS



P32CS

FINN-POWER SERVICE LINE MACHINES FOR FIELD SERVICE

P20CS & P32CS – COMPACT FOR FIELD SERVICE

Portability and usefulness in service vehicles and in demanding equipment in various industries make them ideal for field service and emergency repairs. CS range machines are battery powered with 12V or 24V.

OPTIONS P20CS & P32CS

- Tool base with quick change tool
- Mechanical backstop device
- Tool rack with quick change tool



<http://powerco.lillbacka.com/products/service-line>

DIE SET TABLE P20

Pno	Crimp. range	D	L
18013/10	10.0 - 12.0	10	55
18013/12	12.0 - 14.0	12	55
18013/14	14.0 - 16.0	14	55
18013/16	16.0 - 19.0	16	55
18013/19	19.0 - 23.0	19	55
18013/23	23.0 - 27.0	23	55
18013/27	27.0 - 31.0	27	70
18013/31	31.0 - 36.0	31	70
18013/36	36.0 - 41.0	36	75
18013/41	41.0 - 47.0	41	75
18013/47	47.0 - 54.0	47	85
18013/54	54.0 - 61.0	54	85

DIE SET TABLE P32

Pno	Crimp. range	D	L
18506/10	10.0 - 12.0	10	55
18506/12	12.0 - 14.0	12	55
18506/14	14.0 - 16.0	14	55
18506/16	16.0 - 19.0	16	55
18506/19	19.0 - 22.0	19	55
18506/22	22.0 - 26.0	22	70
18506/26	26.0 - 30.0	26	70
18506/30	30.0 - 34.0	30	70
18506/34	34.0 - 39.0	34	75
18506/39	39.0 - 45.0	39	75
18506/45	45.0 - 51.0	45	90
18506/51	51.0 - 57.0	51	90
18506/57	57.0 - 63.0	57	100
18506/63	63.0 - 69.0	63	110
18506/69	69.0 - 75.0	69	110
18506/74	74.0 - 80.0	74	110
18506/78	78.0 - 87.0	78	110

	P20CS	P32CS
Crimping range (mm) ¹⁾	10–61	10–87
Crimping range (inch) ¹⁾	0.39–2.40	0.39–3.42
Max. opening (mm)	+25	+33
Max. crimping force (kN)	1370	2000
Max. crimping force (tonnage)	137	200
Number of crimpings / hour ²⁾	250	150
Motor (kW)	1.6 / 2.2 ³⁾	1.6 / 2.2 ³⁾
Motor (HP)	2.1 / 3.0 ³⁾	2.1 / 3.0 ³⁾
Weight (kg)	83	116
Weight (lbs)	183	256

1) With standard dies. Crimping range can be increased with special dies.

2) Theoretical with 10 mm cycle.

3) 1-phase / 3-phase.