



# CM30

CM30 is designed for workshop use. CM30 is manually operated and easy to use and it comes with a fume exhaust connection.

3-phase and 1-phase electric configurations available.

Please also see product cards for other CM30/35 configurations.

## TECHNICAL DATA

Max. hose size (inch) <sup>1)</sup>	2 / 1 1/4
Diameter (blade) external	300x3
Diameter (blade) internal	30
Max. hose OD	70
Exhaust outlet OD (mm)	60
Motor Power (kW) <sup>2)</sup>	3.0/2.2
Motor Power (HP) <sup>2)</sup>	4.0/2.9
Velocity, 50Hz	2750
Velocity, 60Hz	3370

## DIMENSIONS (LxWxH)

mm	600x503x739
inch	23.6x19.8x29.1

## WEIGHT

kg/lbs	42/92.4
--------	---------

1) Hydraulic hose, 1-2 wire / 4 wire  
2) 3-phase / 1-phase

## STANDARD FEATURES

Toothed blade

## OPTIONS

Smooth blade

Motor brake (CM30B)

Pneumatic pusher (CM30P)



Toothed blade  
as a standard feature.



Smooth blade  
as an option.

**FURTHER INFO ON OPTIONS,  
PLEASE REVERT TO SPECIFIC PRODUCT CARD**

[POWERCO.LILLBACKA.COM](http://POWERCO.LILLBACKA.COM)